

1	2	***PCB***		
2	1	02-04-160-1101; HARTING VME CONNECTOR 160-PIN FEM	5.00	5.0
3	1	09-73-196-6801; HARTING VME CONNECTOR 96-PIN FEMA	5.00	5.0
4	8	3314-6602; 3M CONNECTOR 14-PIN STRAIGHT.	3.25	26.0
5	10	3428-6602; 3M CONNECTOR 20-PIN STRAIGHT.	2.00	20.0
6	2	3431-6602; 3M CONNECTOR 34-PIN STRAIGHT.	3.50	7.0
7	9	3793-6602; 3M CONNECTOR 10-PIN STRAIGHT.	1.80	16.2
8	1	AT17C512A; ATMEL SERIAL PROM	20.00	20.0
9	1	BD04; CK 4 POSITION DIP SWITCH 81F999; NEWARK PAR	1.85	1.8
10	1	BDG1A16NB; AGERE DIFF LINE DRV	5.00	5.0
11	38	BRR1A16NB; AGERE DIFF. LINE REC.	5.00	190.0
12	56	C1206C104K5RAC; KEMETCAP, 0.1UF 50V SM1206.	0.14	7.8
13	12	DS90C032BTM; NATIONAL SEMI. QUAD LVDS RECEIVER. S	5.00	60.0
14	8	ECS-T1DC106R; PANASONIC CAP, TANT. 10UF 20V SMD	1.00	8.0
15	1	HLMP-6500-012; H.P. LED GREEN. SMD		
16	6	RM73B2AT103J; KOA RM73B2AT103J 10K 100MW SMD RESI	0.10	0.6
17	1	RM73B2AT331J; KOA RM73B2AT331J 330 OHM 100MW SMD	0.10	0.1
18	1	XCS40-3PQ208C; XILINX SPARTAN FPGA	50.00	50.0

				422.5-