




The Status of the Pierre Auger Observatory

Bruce Dawson
University of Adelaide, Australia
for the Pierre Auger Observatory Collaboration



Plan




PIERRE
AUGER
OBSERVATORY

- Description of the observatory
- Physics aims
- History and Schedule

- A Hybrid detector - why?


- Surface Detectors - Aperture and Resolution
- Fluorescence Detectors
- Hybrid Reconstruction - Aperture and Resolution


- First events and preliminary reconstruction





Physics issues with Auger:

- Where does the spectrum end ?
Is there a GZK cutoff?
Are the sources local (<150 Mly)?
- Primary nature (composition) ?
Nuclei? Protons ?
Gamma rays? Neutrinos? Or...?
- What is the source of UHECR ?
Bottom-Up or Top-Down scenario ?





Northern hemisphere
Millard county
Utah, USA



Southern hemisphere:
Malargüe
Provincia de Mendoza
Argentina

Collaboration:


>250 researchers

from 30 institutions and 19 countries:


Argentina, Armenia, Australia, Bolivia,
Brazil, Chile, China, Czech Republic, France,
Germany, Greece, Italy, Japan, Mexico,
Poland, Russia, Slovenia, United Kingdom,
United States of America, Vietnam



The Observatory




PIERRE
AUGER
OBSERVATORY




- Mendoza Province, Argentina
- 3000 km², 875 g cm⁻²
- 1600 **water Cherenkov detectors** 1.5 km grid
- 4 **fluorescence eyes** - total of 30 telescopes each with 30° x 30° FOV

65 km


Pierre Auger - a major step



- **Need high statistics**
large detection area : $2 \times 3000 \text{ km}^2$
- **Uniform sky coverage**
2 sites located in each hemisphere
Argentina and USA
- **Hybrid detector :**
surface array (water Cerenkov tanks)
+ fluorescence detector
⇒ **Good energy and pointing resolution,**
Improved sensitivity to composition
Energy cross calibration



History and Schedule




PIERRE
AUGER
OBSERVATORY

- August 1991 - concept born
- October 1995 - base design complete
- March 1999 - ground-breaking at southern site



History and Schedule




**PIERRE
AUGER**
OBSERVATORY

- January 2000 - beginning of construction
- Feb 21, 2000 - deployment of first detector



- May 23, 2001 - observation of first fluorescence event
- August 2, 2001 - first surface detector event observed

Schedule at Southern site




PIERRE
AUGER
OBSERVATORY


- **2000 and 2001** - “Engineering Array” 40 surface detectors and two fluorescence telescopes

- **2002-2004**
 - full production and deployment, and staged turn on of data-taking

Schedule & Deployment Rate




Reason for winter slow-down




**PIERRE
AUGER**
OBSERVATORY




Engineering Array



PIERRE
AUGER
OBSERVATORY




Why a Hybrid Observatory?



PIERRE
AUGER
OBSERVATORY


- Hybrid resolution of arrival directions, energies and masses is **superior** to that achieved by the SD or a single FD eye independently
- Rich set of measurements on each hybrid EAS
- SD and FD measure cosmic ray parameters using **different methods** with **different systematic errors**
 - Cross-checks and control of systematics.
- while the FD only operates with a duty cycle of 10%, the Hybrid observations will allow **confident analysis of SD data** taken without FD coverage.

e.g. Measurements of Energy



- **SD alone:** E from estimates of water Cherenkov density 1000m from the shower core
 - requires conversion factor from EAS simulations
- **FD alone:** E from estimates of energy deposition in the atmosphere (light \propto dE/dX).
 - requires knowledge of atmospheric transmission.
- two methods can be compared with Hybrid
 - Checks **simulations** and measurement **systematics**

Surface Detectors




PIERRE
AUGER
OBSERVATORY




- 10 m², 1.2 m depth, 3 PMTs, 40 MHz FADC
- Integrated signal expressed in units of **vertical equivalent muons** (1 vem ~ 100 pe)

- for SD-only operation, typically will require **5 stations** at the **4 vem** trigger level (< 20 Hz per station)
- standard techniques for direction and core finding. Several LDFs under study, including a modified Haverah Park function.





Surface Detectors




PIERRE
AUGER
OBSERVATORY

10^{19} eV proton



- SD water Cherenkov detectors measure **muon**, **electron** and **gamma** components of EAS, the latter especially important at large core distances

Surface Detector Resolution




PIERRE
AUGER
OBSERVATORY

- SD Angular resolution: $E > 10^{19}\text{eV}$

θ (deg)	Proton/Iron		Photon
	$E > 10^{19}\text{eV}$	$E > 10^{20}\text{eV}$	$E > 10^{19}\text{eV}$
20°	1.1°	0.6°	4.0°
40°	0.6°	0.5°	2.5°
60°	0.4°	0.3°	1.0°
80°	0.3°	0.2°	1.0°


space angle containing 68% of events

Surface Detector Resolution




PIERRE
AUGER
OBSERVATORY

- Energy determined from fitted density at 1000m, $\rho(1000)$. Conversion factor from simulations; averaged for p and Fe primaries. $E > 10^{19}$ eV



rms E resolution $\sim 12\%$ (assuming p/Fe mixture)

SD Aperture and Event Rate




PIERRE
AUGER
OBSERVATORY


E_o (eV)	Trig Aperture km^2sr	Rate per year $> E_o$
10^{18}	0	0
3×10^{18}	2200	15000
10^{19}	7200	5150
2×10^{19}	7350	1590
5×10^{19}	7350	490
10^{20}	7350	100
2×10^{20}	7350	30

- Zenith $< 60^\circ$, based on AGASA spectrum (Takeda et al 1998)
 - (Zenith $> 60^\circ$ adds about 50% to event rate)

Auger Southern Site



PIERRE
AUGER
OBSERVATORY



• = Fluorescence site


- Hybrid reconstruction works when a shower is recorded by the surface array and **at least one eye**
- This multiple-eye design reduces our reliance on precise knowledge of **atmospheric attenuation of light**
- Mean impact parameter at 10^{19} eV is **13km**




The completed FD building will house 6 telescope/ camera arrays




Fluorescence Detector




PIERRE
AUGER
OBSERVATORY



Schmidt aperture stop




440 pixel camera $30^\circ \times 30^\circ$



3.8m x 3.8m prototype mirror
and camera


Hybrid Reconstruction of Axis




PIERRE
AUGER
OBSERVATORY

- good determination of **shower axis** is vital for origin studies, but also vital as **first step** towards good energy and mass composition assignment
- use eye pixel timing and amplitude data together with **timing information from the SD**.
 - GPS clocks in SD tanks and at FDs.
- Hybrid methods using **one eye** give angular resolution comparable to **“stereo” reconstruction**

Hybrid Reconstruction (Cont.)



- eye determines **plane** containing EAS axis and eye
 - plane normal vector known to an accuracy of $\sim 0.2^\circ$
- to extract R_p and ψ , eye needs to measure angular velocity ω and its time derivative $d\omega/dt$
 - but difficult to get $d\omega/dt$, leads to degeneracy in (R_p, ψ)
- degeneracy broken with measurement of **shower front arrival time** at one or more points on the **ground**
 - eg at SD water tank positions





Hybrid Reconstruction (Cont.)


- Simulations at 10^{19}eV
- Reconstruct impact parameter R_p . Dramatic improvement with Hybrid reconstruction

median
 R_p error = 350m

strong
dependence on
angular “Track
Length”





Simulated Hybrid Aperture



PIERRE
AUGER
OBSERVATORY


Hybrid Trigger
Efficiency



“Stereo”
Efficiency

- Note the significant aperture at 10^{18}eV , and the **stereo aperture** at the higher energies
- **Trigger requirement:** at least one eye triggering on a track length of at least 6 degrees; two surface detectors. $\theta < 60^\circ$
- **Hybrid Aperture** = Hybrid Trigger efficiency x $7375 \text{ km}^2\text{sr}$

Hybrid Reconstruction Quality



PIERRE
AUGER
OBSERVATORY

E(eV)	Δ_{dir} ($^{\circ}$)	Δ_{Core} (m)	$\Delta E/E$ (%)	ΔX_{max} g/cm 2
10^{18}	0.7	60	13	38
10^{19}	0.5	50	7	25
10^{20}	0.5	50	6	24

statistical
errors only

zenith
angles < 60 $^{\circ}$

- **68%** error bounds given
- detector is optimized for 10^{19} eV, but good Hybrid reconstruction quality **at lower energy**



Assembly Building


Official ribbon cutting, Nov. 2000




Open house for the public




Office Building Opening Nov 2001




**PIERRE
AUGER**
OBSERVATORY



“First Light” 23 May 2001




PIERRE
AUGER
OBSERVATORY




first large
shower in
Auger FD
23.05.2001

85 degree zenith angle event




PIERRE
AUGER
OBSERVATORY



Jan 6 2002

First 7-fold
coincidence

All tank
signals
sharp in
time (as
expected)



PIERRE
AUGER
OBSERVATORY

“Gold”
event
Jan 17
2002

Event Display

Ground Array Events Configuration

Control

File Select trigger Search events

Reconstruct Next Event Update 1 Triggered

#00106018: Thu Jan 17 02:34:41 2002	#0063 (829286705 ns)
#00106023: Thu Jan 17 02:41:19 2002	#0036 (829285360 ns)
#00106032: Thu Jan 17 02:49:32 2002	#0049 (829283597 ns)
#00106078: Thu Jan 17 03:26:12 2002	#0064 (829283596 ns)
#00106138: Thu Jan 17 04:09:45 2002	
#00106216: Thu Jan 17 05:25:24 2002	
#00106283: Thu Jan 17 06:24:22 2002	

6 FADCs Bad stations

Array

Status

file selected: eb_2002_01_17_02h18.root
Minimum number of triggered stations: 1
Trigger selected: FD Los Leones

Display


Lateral distribution function fit

Distance (m)	Signal (VEM)
470	47 ± 10
480	60 ± 15
500	45 ± 10
700	15 ± 5

$dX = 65m$
 $dY = 110m$

$Theta = 40.1 \pm 1.4 \text{ deg}$
 $Phi = -13.9 \pm 10.8 \text{ deg}$

$S(1000) = 4.37 \pm 1.5 \text{ VEM}$
 $E = 1.1 \text{ EeV} \pm 34\%$



Trace. Col 12. Row 12


Trace. Col 11. Row 11

Trace. Col 9. Row 9

Trace. Col 8. Row 7

Trace. Col 11. Row 10

Trace. Col 15. Row 17



Display

- Single selection
- Multiple selection
- Virtual Channel

Event

- Event 522 - Run 330
- Event 530 - Run 330
- Event 534 - Run 330**
- Event 536 - Run 330
- Event 537 - Run 330
- Event 544 - Run 330



Clear

Keep...

19 pix. trig.
 T3Id 4102
 GPS Time 695270985
 GPSNanoTime 829298000

Trigger


Second Level Trigger



**PIERRE
 AUGER**
 OBSERVATORY


“Gold”
 event
 Jan 17
 2002

Laser Shots




PIERRE
AUGER
OBSERVATORY

- Probing atmospheric transmission 300-400 nm
- Calibration tool




Laser Shots - calibration



- 355nm vertical laser 3km from detector



Black - real data
Red - simulation



PIERRE AUGER OBSERVATORY



- Display
- Single selection
 - Multiple selection
 - Virtual Channel


Event

Event 2373 - Run 226

Clear


Keep...

23 pix. trig.
 T3Id 4132
 GPS Time 692086569
 GPSTime 200370100





Hybrid event.

Since Dec 2001



PIERRE AUGER OBSERVATORY



- Display
- Single selection
 - Multiple selection
 - Virtual Channel
 - Pedestal Subtraction


Event

Event 1461 - Run 217



Clear

Keep...

25 pix. trig.
T3ld 4118
GPS Time 691991975
GPSNanoTime 358692100



Hybrid event rate ~ 1 per two hrs




**PIERRE
AUGER**
OBSERVATORY

Cerenkov
contaminated



Dec 12, 2001
Hybrid trigger

43 fired pixels
in camera





Result of hybrid
geometric
reconstruction

zenith angle = 25.8 deg
core distance = 11300 m




PIERRE
AUGER
OBSERVATORY

collected charge
(photoelectrons)
vs time.
Total time approx $20\mu\text{s}$




PIERRE
AUGER
OBSERVATORY

transformed to
shower charged
particle number
vs atmospheric
depth (g/cm^2)



Conclusion



PIERRE
AUGER
OBSERVATORY

- Engineering array is built and operating well.
- second FD building being constructed now, first site fully instrumented (6 telescopes) by Oct 2002.
- next 100 SD installed starting Sep 2002
- expect full observatory complete by last quarter 2004
- but data will be pouring in well before from partially completed system.