SLAC-PUB-1487 HEPL 739 September 1974 (E)

RELATIVE VELOCITY MEASUREMENTS OF ELECTRONS

AND GAMMA RAYS AT 15 GeV

and then give a 1/1

Aligned and the Hill of the god

Z.G.T. Guiragossian, G. B. Rothbart, and M. R. Yearian

Department of Physics and High Energy Physics Laboratory* Stanford University, Stanford, California 94305

and

R. A. Gearhart and J. J. Murray

Stanford Linear Accelerator Center[†] Stanford University, Stanford, California 94305

ABSTRACT

Measurements were made to detect differences in the velocity of propagation of gamma rays and electrons in the energy range 15 - 20 GeV, using a time-of-flight technique with 1 psec sensitivity and a flight path of ~1 km. A relative velocity difference larger than $1-\beta_e$ $(\sim 5 \times 10^{-10})$ would imply a breakdown of special relativity. No significant difference in the velocities of light and electrons was observed to within ~2 parts in 10^7 .

(Submitted to Phys. Rev. Letters.)

*Work supported in part by the National Science Foundation (Grant GP-38611). †Work supported by the U. S. Atomic Energy Commission. Previous efforts have been made to detect a frequency dependent shift in the velocity of light from visible wavelengths up to GeV energies. All such experiments are in essence attempts to detect some departure from the predictions of special relativity.

The most recent contribution preceding the present work was made by Brown <u>et al.</u>¹ Using a time-of-flight (TOF) technique, they compared the velocities of short pulses of visible light and 7 GeV gamma rays. The results gave a relative velocity difference of $(1.8 \pm 6) \times 10^{-6}$. An additional measurement using 11 GeV electrons and visible light gave a relative velocity difference of $(-1.2 \pm 2.7) \times 10^{-6}$. The precision of these measurements was limited in part by the time resolution of photomultiplier detectors.

In the present experiment at the Stanford Linear Accelerator Center (SLAC) the relative velocities of ~15 GeV gamma rays and electrons with energies ranging from 15 to 20.5 GeV were measured using an rf separator (RFS) synchronized with the accelerator's rf system as the timing element. Ultimate time resolution was limited, in part, by the characteristic bunch length of SLAC beams, ~5 psec or 5 degrees of rf phase. Results more than one order of magnitude smaller in $\Delta v/c$ at energies higher than the previous best measurements were achieved.

Electrons accelerated to 15 GeV in about 2/3 of the full length of the accelerator strike a thin, annular target at the end of Sector 22, scatter and produce bremsstrahlung photons (Fig.1a). Measurements were made both with and without further acceleration. With acceleration, electron energy increased continuously to 20.5 GeV at the end of the accelerator. After a common flight path of 1015 meters a small fraction of the photons and scattered electrons strike two thin targets which serve as positron sources for the beam transport system (Fig. 1b).

-2-

The upstream (downstream) target fills the upper (lower) half of the beam aperture. Their axial displacement within the field of vertical bending magnet B60, in conjunction with subsequent collimation and momentum analysis, is such that only 13.5 GeV positrons produced by electrons (photons) in the upper (lower) target are retained in the transport system. Images of the upper (lower) target cover the lower (upper) slits of a dual slit collimator located at F1. This collimator is in turn imaged on the detector at the second focus of the secondary beam just downstream of the RFS. The final images consist of two horizontal strips where positrons comprising the upper (lower) image were produced by electrons (photons). The RFS provides an effective transverse deflecting field uniform over the waveguide aperture, ² imparting a transverse momentum to an extremely relativistic particle dependent only upon the particle's arrival time relative to the RFS phase. With phase set for null deflection the maximum deflection sensitivity at 13.5 GeV/c is 0.0070 in. per degree of phase, or 0.0068 in./psec.

Thus, an $e^-\gamma$ TOF difference would be manifested as a change in the separation of the $e^-\gamma$ images when the RFS is turned on. The typical FWHM of the images was 0.070 in. with approximately equal contributions from random phase spread, finite image size and miscellaneous aberrations. This width corresponds to $\Delta v/c \sim 1.5 \times 10^{-6}$ for a drift length of 1015 meters. Random TOF differences between $e^-\gamma$ positrons within the secondary beam transport system (due mainly to horizontal dispersion) have an rms value ~1 psec. The correlated TOF difference (due to the fact that e^- and γ positrons occupy different regions of phase space in the vertical plane) was <0.1 psec and would simulate the effect of a true $(v_e - v_\gamma)/c \sim -3 \times 10^{-8}$.

- 3 -

It is an important fact that the beam striking the target at Sector 22 is scattered by angles large compared to the acceptance angle of the B60 targets and consequently that the time phase of both the electrons and γ 's at B60 is statistically representative of the average time phase of the incident electron beam with negligible uncertainty. We believe that on one occasion we experienced an effect due to anomalous electron flux from a portion of the beam passing through the center of the annular target, but on most occasions we are also certain such an effect could not have occurred because electron beam steering at Sector 22 was such that an unscattered beam could not have been transmitted to the B60 targets. No other systematic effects known to us could have affected the measurements significantly.

Background photons produced beyond the Sector 22 target could not be identified during a measurement. But an attempt was made to estimate the highest possible background contamination before and after each run by steering the beam into the walls of the accelerator downstream of Sector 22 with the target removed. Under these conditions, the electron rate was negligible, while the γ rate fell to about 15% of normal. We have made the conservative assumption that the worstcase background (15%) prevailed in all measurements and corrected our timing sensitivity accordingly.

A multiwire proportional chamber (MWPC) located at the second focus measured the vertical coordinate of each positron on an event-by-event basis. The differential linearity of the device is measured to be about 40 microns (0.0016 in.). The resolution for a single event can be estimated to be 100 microns (0.0040 in.) from the intrinsic signal:noise limitation of the position encoding electronics. More detailed discussions of the beamline and the MWPC as well as theoretical implications of the results can be found elsewhere.^{3,4}

- 4 -

Figure 2 shows the profile obtained with an 55 Fe double slit test source (0.020⁻in. slits with a mean separation of 0.2998 in.). Figures 2b, c show the typical γ (e⁻) profile obtained with the γ (e⁻) targets separately, demonstrating that crosstalk between images is negligible.

A large number of independent measurements were made each consisting of three sets of $e^-\gamma$ profiles, one with RFS off, and two with RFS on, one at each of the two maximally sensitive phases. The data were analyzed by two methods:

<u>Method 1</u>. The coordinates of all events are histogrammed and the separation of the γ and e⁻ images is determined for each RFS phase by fitting the double-peaked profiles (Fig. 2d) with convenient line shapes parametrized in terms of the amplitude, mean and width of the two images. The relative e⁻- γ velocity difference deduced from such a measurement can be expressed as

$$\Delta \mathbf{v}/\mathbf{c} = \pm \mathbf{A}^{-1} \cdot \mathbf{f} \cdot (\mathbf{S}^{\pm} - \mathbf{S}^{\circ}) / \mathbf{L} \mathbf{c}$$

$$= \mathbf{A}^{-1} \cdot \mathbf{f} \cdot (\mathbf{S}^{\pm} - \mathbf{S}^{-}) / 2\mathbf{L} \mathbf{c} \quad .$$
(1)

where S^{\pm} is the $e^{-\gamma}$ peak separation in each of the two maximally sensitive RFS phase settings, S^{0} is the RFS-off peak separation, A is the deflection sensitivity of the RFS, L is the drift length, and 1 < f < 1.6 is a correction factor that accounts for the assumed 15% gamma background and losses in timing sensitivity due to incomplete temporal overlap of the RFS gating (on occasion part of the beam spill was accidentally allowed to fall outside the RFS pulse). For each complete set of data $S^{+}-S^{-} = \Delta S$ and $\Delta v/c$ is determined.

Method 2. Using the same data as above, the difference of coordinates of electron and gamma events that occur only in temporal succession, at constant RFS phase, is histogrammed. This yields a single peak profile (Fig. 2e) with a well-defined mean that does not require fitting, and is entirely independent of

-5-

RFS phase and steering changes occurring over times long compared to the time between events.

Averages and standard deviations of $\Delta v/c$ for all independent measurements in each of several different experimental conditions are then calculated with statistical weighting. For Method 1, the observed spread of ΔS_i was typically the order of twice the expected statistical fluctuation whereas for Method 2, the observed and statistical standard deviations agree. This indicates that timedependent fluctuations of unknown origin in the separation of the images (comparable in magnitude to our statistical uncertainties) did occur, but that by comparing only events that are temporal neighbors the effects of these fluctuations are entirely removed.

In Table I results obtained in each of the experimental configurations is given. The first entry in the table is the result of a test in which the B60 targets are removed and a conventional target (TC60 in Fig. 1a) is used instead to uniformly illuminate the dual slit collimator at F1. This simulates the " $e^--\gamma$ " beams in the last stage of the system and was done primarily to demonstrate the potential precision of the experiment.

The second entry is the result of another test where a thin target (PR2 in Fig. 1a) located a short distance upstream of B60 is used instead of the Sector 22 production target. This was done to check $e^--\gamma$ identification, isochronism of the positron beam line, and mechanics of data taking.

The remaining results shown in the table are obtained in the final experimental configuration with Sector 22 production target in place, and using the full drift length of 1015 meters. In experiment number 3, electrons drift the last third of the accelerator, while in 4 and 4' they are accelerated to 20.5 GeV.

- 6 -

In 4, anomalous data obtained on one occasion due to targeting difficulties at Sector 22 are omitted, while in 4' all data are included.

Taken as a whole, we interpret these results to indicate equality of the velocities of propagation of gamma rays and electrons in the energy range 15-20 GeV to within ~2 parts in 10^7 , where a relative difference greater than $1-\beta_e=5\times10^{-10}$ would be significant.

The authors acknowledge Dr. R. Miller for his indispensable aid in tuning the accelerator to meet the novel requirements of this experiment. We also wish to thank the Accelerator Operations Group, especially Mr. R. Hanselman, Mr. T. Inman, and Mr. J. Harold for their patient cooperation, Dr. G. Ispirian for helping to motivate the experiment, and Dr. T. G. Pavlopoulos for discussion regarding the theoretical aspects of the experiment.

REFERENCES

- B. C. Brown, G. E. Masek, T. Maung, E. S. Miller, H. Ruderman, and W. Vernon, Phys. Rev. Letters 30, 763 (1973).
- O. H. Altenmueller, R. R. Larsen, and G. H. Loew, Rev. Sci. Instr. <u>35</u>, 438 (1964).
- Z.G.T. Guiragossián, G. Rothbart, M. R. Yearian, R. Gearhart, and
 J. J. Murray, IEEE Trans. Nucl. Sci. <u>NS-20</u>, 994 (1973).
- 4. Z.G.T. Guiragossián, G. B. Rothbart, M. R. Yearian, R. Gearhart, and J. J. Murray, SLAC-TN-74-12 (1974, unpublished).

TABLE CAPTION

I. Experimental results: difference of the high phase and low phase $e^-\gamma$ peak separations, arrival time difference corrected for timing sensitivity, and the relative $e^-\gamma$ velocity difference inferred therefrom. Uncertainties are observed standard deviations for the number of measurements indicated.

FIGURE CAPTIONS

- 1. a) Accelerator and beam transport systems (vertical plane).
 - b) Separation of e^- and γ beams and rejection of background at the conversion targets within the magnetic field of B60 (vertical plane).
- 2. Detector performance and typical experimental data. One channel represents 6.4×10^{-3} inches.
 - a) 55 Fe double slit position spectrum.
 - b) γ image alone (e⁻ conversion target removed).
 - c) e image alone (γ conversion target removed).
 - d) Typical experimental spectra of e^{-1} and γ images.
 - e) Difference spectra of above data (in this example, one channel represents 0.55 psec).



(ь)

Fig. 1



Fig. 2