

- ABA (*see* Aatron-Blume-Atkinson)
- Absorption devices, 705–771
- Accelerator components and systems
 - alignment system, 65, 66, 821–885
 - cooling water, 71, 72, 935–988
 - drive and phasing, 70, 271–301, 383–409
 - high power modulators, 69, 411–462
 - injector, 69, 70, 241–269
 - instrumentation and control, 74–78, 489–544
 - klystrons, 66–68, 303–344
 - positron source, 72–74, 545–583
 - structure, 63–65, 95–162
 - vacuum system, 70, 71, 887–933
- Accelerator design
 - economic considerations, 100
 - electric gradient, 100
 - feed interval, 101–103
 - frequency, choice of, 95
 - frequency, dependence of machine parameters on, 96
 - length, 99
 - repetition rate, 104
 - RF power sources, 101
 - RF pulse length, 103, 104
- Accelerator housing, 1121–1124
- Accelerator structure, 63–65, 95–162
 - attenuation parameter, 115
 - beam loading, 116
 - cold test, 131, 132
 - constant gradient, 109–115
 - constant impedance, 109–115
 - conversion efficiency, 117
 - coupled resonator wave, equations for, 120, 121
 - coupler asymmetry, 144–148
 - elementary principles of operation, 60–62
 - empirical design of, 126–136
 - energy loss in idle sections, 118
 - fabrication, 148–157
 - filling time, 118
 - filter characteristics, 119, 120
 - frequency sensitivity, 118
 - group velocity, 118, 133, 134
 - matching, 136–142
 - operating mode, 104–108
 - phase velocity, 61, 62, 133
 - Q , 135
 - space harmonic amplitude, 135
 - transient behavior, 123–125
 - tuning, 136–142, 153–157
- Accelerator support system, 821–885
 - accelerator sections, 849–583
 - beam analyzing stations, 858, 859
 - beam switchyard, 867–882
 - alignment of components, 877–882

- calculations, 869, 870
 - laser reference line 869,
 - requirements, 867, 868
 - support stands, 875–877
 - tape bench, 873–875
- beam switchyard support girders, 860
- design criteria, 844–846
- drift sections, 853–855
- injector girder, 858
- installation, 861–866
- laser alignment hardware, 848, 849
- light pipe vacuum restraints, 860, 861
- monument target system, 855, 856
- positron source girders, 857, 858
- quadrupole singlets, 859, 860
- twenty-four inch light pipe, 846–848
- Administration, 39–53
 - fiscal experience, 47–52
 - manpower, 52
 - organization, 39–45
 - scheduling, 45–47
 - staff classification, 41–43
- Administration and engineering building, 1102–1104
- Aetron-Blume-Atkinson, 34
- Alignment system, 65, 66, 821–885
 - (*see also* Accelerator support system)
- Altenmueller, O., 211
- Amplitron, 303, 304
- Antiparticles, 10
- Architecture, buildings, 1099, 1100
- Asymmetry, coupler, 144–148
- Atomic Energy Commission, 7, 8
- Attenuation parameter, 115
- Auditorium, 1104, 1105

- Barber, W. C., 32
- Beam absorption devices, 705–771
- Beam analyzing stations, 193, 522–529
 - (*see also* Instrumentation and control)
- Beam breakup, 88, 89, 115, 203–237
 - coupled resonator model, 209
 - differential equation, 207
 - effect of focusing, 209
 - effects of space charge, 204
 - isolated cavity model, 214–216
 - multicavity model, 206
 - numerical computation, 209
 - observation and experimental laws, 217–233
 - remedies, 234–237
 - brute force, 235
 - choice of, 235
 - improvement in threshold, 235–237
 - Landau damping, 234
 - RF cancellation, 234
 - RF fixes, 234
 - starting noise suppression, 234
 - resistive wall effects, 204
 - starting sources, 207
 - theory and calculations, 203–217
- Beam characteristics, 84–89
- Beam control system, 193–202
 - beam analyzing stations, 193
 - degaussing and magnetic shielding, 193
 - description, 195, 196
 - effects of magnetic fields, 195–197
 - long ion chamber, 193
 - standard drift section
 - beam intensity monitor, 194
 - beam position monitor, 193
 - beam profile monitor, 194
 - beam scraper, 194
 - quadrupole doublet, 193
 - reference cavity, 193
 - steering dipole, 194
- Beam current monitor, 625–658
- Beam deflectors, injector, 257–259
- Beam dynamics, 163–237
 - equations of motion, 163–166
 - external focusing, 166–192
 - phase space, 167–169, 201, 202
- Beam guidance system, 517–520
- Beam induction technique (*see* Phasing)
- Beam interaction with materials, 706–717
 - cascade shower development, 706–709
 - heat transfer problems, 712–715
 - low power dump, 727, 729
 - design, 728, 729
 - power deposition and temperature rise, 709–712
 - thermal fatigue, 716, 717
 - thermal shock, 717
 - thermal stress development, 715, 716

- (*see also* Radiation damage to components)
- Beam knockout system, 69, 484
- Beam loading, 116
- Beam monitoring system, 500–516
(*see also* Instrumentation and control)
- Beam switchyard, 78–80, 585–615, 1129–1134
- beam current monitor, 652–658
 - beam monitors, 651
 - description, 585–589
 - design, 609–612, 651, 652
 - equipment protection system, 651
 - instrumentation, 651–704
 - interlock system, 687–694
 - description, 687, 688
 - differential current interlock, 694
 - electronics, 688, 689
 - ionization chamber, 689–691
 - pulsed magnet, 693, 694
 - thermal protection, 691, 692
 - magnet power supplies, 651
 - magnets, 611, 612
 - operating experience, 612, 613
 - position monitors, 658–660
 - profile monitors, 660–666
 - Cerenkov light, 662, 663
 - optics and TV system, 665–667
 - synchrotron light, 660–662
 - zinc-sulfide screens, 664, 665
 - secondary emission monitors, 667, 668
 - shielding, 608, 609
 - spectrum instrumentation
 - drift indicator, 673
 - spectrum analyzer, 671, 672
 - tune-up monitor, 670
 - support and alignment system (*see* Accelerator support system)
 - transport and momentum analysis, 589–593
 - transport control system, 651
 - transport system
 - A and B, 591, 592
 - alignment, 602–604
 - computer, 675–682
 - control, 673–687
 - design, 593–599
 - induced radioactivity, 607, 608
 - magnetic measurements, 674, 675
 - manual magnet control, 673, 674
 - optimization of system A, 599–601
 - primary radiation, 606
 - secondary radiation, 606, 607
 - selection of parameters, 592, 593
 - slit/collimator control, 683–687
 - thermal effects, 605, 606
 - vacuum system, 610, 916–929
 - water systems, 610, 972–988
- Beam transport system, 166–192
- adiabatically varying, 171, 172
 - choice of, 187, 188
 - description, 197, 198
 - effects of quadrupole misalignment, 179–181
 - equation of motion, 169
 - error analysis of, alternative systems, 181–187
 - injector, 266–268
 - matrix formulation, 169, 170
 - operation, 200
 - periodic, 170
 - properties of alternative types of, 173–179
 - transport properties, 199, 200
 - transverse perturbations
 - accelerator misalignment, 191, 192
 - coupler asymmetry, 190, 191
 - scattering by residual gas, 188
 - stray magnetic fields, 189, 190
- Becker, G. E., 28
- Betatron, 27
- Bohr, N., 10
- Brown, K. L., 28, 32
- Bubble chambers, 24, 25
- Buildings, 55–57, 1095–1149
- accelerator housing, 1121–1124
 - administration and engineering, 1102–1104
 - architectural considerations, 1099, 1100
 - auditorium and cafeteria, 1104, 1105
 - beam switchyard, 1129–1134
 - central control building, 1127, 1128
 - central laboratory, 1106–1108
 - central utility building, 1117, 1118
 - crafts shop, 1115, 1116
 - cryogenic laboratory, 1109–1111

- data assembly building, 490, 1134, 1135
- electrical substations, 1118, 1119
- electronics building, 1114, 1115
- fabrication building, 1113, 1114
- fire station, 1119, 1120
- general services building, 1116, 1117
- heavy assembly building, 1112, 1113
- klystron gallery, 1124–1126
- laser room, 1128, 1129
- master plan, 1095, 1096
- research area, 81, 82, 1135–1150
 - B-beam line, 1146
 - beam dump east, 1143, 1144
 - counting house, 1139
 - end station A, 1139–1142
 - 54-inch spark chamber, 1149
 - 40-inch bubble chamber, 1149
 - portable, 1149, 1150
 - streamer chamber, 1143
 - yard, 1137–1139
- shops dining room, 1115
- shops and support buildings, 1111–1135
- space requirements, 1096–1098
- structural design, 1100
- temporary computer facility, 1108, 1109
- test laboratory, 1101, 1102
- Bunker, F. W., 29

- Cafeteria, 1104, 1105
- Cascade shower development, 706–709
- Caswell, D. A., 28
- Central control (*see* Instrumentation and control)
- Central control building, 1127, 1128
- Central laboratory, 1106–1108
- Central utility building, 1117, 1118
- Characteristics, beam, 84–89
- Chodorow, M., 28, 29
- Chu, E. L., 27, 29
- Collimators and slits, 730–770
 - actuation and drive, 750–759
 - high power, 731–746
 - high Z, 746–750
 - protection collimators, 759–770
- Conservation, 11
- Constant gradient, 109–115
- Constant impedance, 109–115
- Conversion efficiency, 117
- Cooling water systems, 71, 72, 935–988
 - accelerator systems, 943–968
 - B-beam target, 976–978
 - beam switchyard and end stations, 610, 972–988
 - cooling towers, 968
 - disk-loaded waveguide, 945–952
 - distilled water plant, 940, 941
 - general purpose, 936–940
 - klystron, 955–959
 - magnet coil, 972–974
 - magnet power supplies, 974, 975
 - operating experience, 969–971, 986, 987
 - positron source, 959–968
 - pulsed magnets, 976
 - radioactive systems, 978–982
 - rectangular waveguide, 952–955
 - target area, 982–985
- Coupler asymmetry, 144–148
- Crafts shop, 1115, 1116
- Cryogenic laboratory, 1109–1111
- Current monitor, beam, 652–658

- Data assembly building, 490, 1134, 1135
- Data handling system, 529–538
- Debs, R., 32
- Degaussing, 193–197
- Dirac, P. A. M., 10
- Directional couplers, waveguide, 364–376
- Drell, S. D., 18
- Drift indicator, 673
- Drift section, 193–194
- Drive system, 70, 271–301
 - basic requirements, 271
 - drop out cables, 298, 299
 - frequency multipliers, 275, 288–291
 - $I\phi A$ unit, 275, 297, 298
 - main booster amplifier, 275, 279–281, 299, 300
 - main drive line, 275, 281–287
 - master oscillator, 274–278, 299
 - standby equipment, 299, 300
 - sub-booster klystron, 292, 293
 - sub-booster modulator, 275, 293–296, 300

- sub-drive line, 275, 287, 288
- switchable phase shifter, 298
- Drop-out cables (*see* Drive system)

- Eldredge, A. L., 28, 29
- Electrical power system, 989–1028
 - emergency power, 1020, 1021
 - fire alarm system, 1016, 1017
 - grounding, 1017–1020
 - operational experience, 1022–1026
 - power consumption, 1024, 1025
 - power contracts, 1024, 1025
 - power costs, 1024, 1025, 1027
 - power factor correction, 1025, 1026
 - primary services
 - master substation, 994–997
 - 220 and 60 kV lines, 992–994
 - secondary distribution
 - beam switchyard, 1005–1007
 - campus facilities, 1015, 1016
 - end station area, 1007, 1008
 - klystron gallery, 1001–1004
 - positron source, 1004, 1005
 - 12.47 kV distribution, 997–1001
- Electrical substations, 1118, 1119
- Electron accelerators, 2
- Electron gun, klystron, 308–310
- Electron gun (*see* Injector)
- Electron scattering, 30
- Electronics building, 1114, 1115
- Emergency power, 1020, 1021
- Erosion control, site, 1092, 1093
- Experiments
 - acceptance, 6
 - criteria for selection, 6
 - execution, 7
 - proposals, 6
 - records, 7

- Fabrication, accelerator structure, 148–157
- Fabrication building, 1113, 1114
- Filling time, 118
- Fire alarm system, 1150, 1151
- Fire station, 1119, 1120
- Flanges, waveguide, 374–376
- Focusing, 167–192
 - (*see also* Beam dynamics)

- Franklin, L. H., 29
- Frequency, accelerator, 95, 96
- Frequency multipliers (*see* Drive system)
- Fresnel lens (*see* Laser alignment system)

- Geisler, W. S., 29
- General services building, 1116, 1117
- Geology, site, 1089, 1090
- Ginzton, E. L., 27–29
- Girder assembly and installation, 157–160
- Group velocity, 118, 133, 134

- Hansen, W. W., 27, 29
- Harrison, A. E., 28
- Heavy assembly building, 1112, 1113
- Herrmannsfeldt, W. B., 244, 262
- Hiestand, N. P., Jr., 28
- High Energy Physics Laboratory, 31
- High power collimators, 731–746
- High power dump, 717–727
 - criteria, 717, 718
 - design, 718–720
 - materials, 723
 - radiolysis and radioactivity, 725–727
 - water system, 723, 724
 - window, 721, 722
- High Z collimators, 746–750
- Hildebrand, R. H., 36
- Hofstadter, R., 18, 30, 32

- $I\phi A$ unit (*see* Drive system)
- Initial operating results, 82–94
- Initial research equipment
 - bubble chambers, 24
 - large analyzing magnets, 24
 - spectrometers, 22
- Injector, 69, 70, 241–269
 - beam structure equipment
 - initial beam deflector, 257–259
 - second beam deflector, 259
 - beam transport, 266–268
 - radial phase space, 267, 268
 - solenoid, 267
 - system description, 266, 267
 - electron gun
 - computer design, 244, 245

- general characteristics, 243, 244
 - mechanical design, 246–249
 - performance, 249–251
 - phase space, 245, 246
- girder, 858
- gun modulator, 253–256
 - bias programming, 254, 255
 - physical design, 253, 254
 - pulse width programming, 255, 256
- microwave system, 259–266
 - accelerator section, 263, 264
 - bunch monitor, 264, 265
 - buncher, 259–263
 - measurement of bunching, 265, 266
 - prebuncher, 263
- modulator, 484
- multiple beam capability, 252–259
- specifications, 241–243
- Instrumentation and control, 74–78, 489–544
 - beam analysis stations, 522–529
 - electromagnet characteristics, 525, 526
 - energy analyzer foils, 526, 527
 - optical design, 523–525
 - beam control concepts, 492, 493
 - beam guidance system
 - controllers, 519, 520
 - power supplies, 517–519
 - beam monitoring system, 500–516
 - beam switchyard monitors, 507–510
 - cavities, 503–507
 - construction and installation, 506, 507
 - data transmission and display, 514–516
 - detector panels, 506, 507
 - end station monitor, 511, 512
 - results, 510, 511
 - sector electronics, 512–514
 - beam profile monitors, 521, 522
 - beam switchyard, 651–704
 - central control, 490
 - description, 538–540
 - maintenance and servicing, 542, 543
 - operation, 540–542
 - programming, 543
 - control requirements, 491–495
 - criteria, 489–491
 - data assembly building, 490
 - data handling system
 - analog, 534–536
 - remote control, 533
 - status monitoring, 529–532
 - video cable, 536–538
 - interlocks, 493, 494, 775–777
 - klystron control, 497
 - klystron-modulator control signals, 497, 498, 500
 - local control areas, 491
 - modulator-klystron protection, 498–500
 - positron source, 577–581
 - signals, 494, 495
 - variable voltage station control, 496, 497
 - (*see also* Protection systems and Trigger system)
- Interlocks, 493, 494, 775–778
 - access controls, 785
 - beam switchyard, 687–694
 - CCR display panels, 789
 - DAB display panel, 788, 789
 - emergency stop circuit, 790, 791
 - machine shutoff system, 783–785
 - personnel accessways, 787, 788
 - special accessways, 788
 - warning signals, 785–787
 - wiring, 790
- Ion chamber, long, 193
- Jasberg, J. H., 29, 32
- Jaynes, E. T., 28
- Jones, C. B., 29
- Kaisel, S. F., 28
- Kennedy, W. R., 28
- Kerst, D. W., 27
- Klystron, 66–68, 303–344
 - collector design, 312, 313
 - compared to amplatron, 303, 304
 - control, 497
 - cooling water system, 955–959
 - design and development, 308–313
 - drive requirements, 272
 - efficiency, 310, 311, 319, 320

- electron gun, 308–310
- gallery, 1124–1126
- interaction space, 310–312
- mechanical design, 314–316
- modulator, 1001
- operating conditions, 337, 338
- operation experience, 338–341
- oscillations, 310–312
- performance, 89–91, 316–320
- procurement, 306, 307
- radiation shielding, 315, 316
- specifications for SLAC, 305, 306
- window
 - assembly details, 326, 327
 - boundary failure, 332, 333
 - breakdown, 320, 323
 - coating, 335–337
 - development, 320–332
 - dielectric failure, 328, 329
 - materials, 322–326
 - multipactor, 333–337
 - testing, 321, 322
 - thermal failure, 329–332
- (*see also* Instrumentation and control)
- Koroza, V. I., 208
- Kyhl, R. L., 29

- Landscaping, site, 1093, 1094
- Larsen, R., 211
- Laser alignment system, 821–844
 - baffles, 840
 - description, 821–824
 - detector, 829–831
 - detector signals, 836–840
 - image pattern, 831–836
 - lens design and fabrication, 824–829
 - light source, 824
 - target intensity maximization, 882–885
 - vacuum requirements, 840–842
- Laser room, 1128, 1129
- Lichtenberg, A. J., 259
- Lisin, A., 350–356
- Loew, G. A., 211
- Long ion chamber, 193

- Machine characteristics
 - beam current, 3
 - beam duty cycle, 14
 - beam energy, 3, 13
 - beam intensity, 14
 - geometrical properties of the beam, 16
 - operational flexibility, 17
 - spectrum width, 14
- Magnet power supplies
 - A bending magnet, 701, 702
 - B bending magnet, 702, 703
 - dc, 697–699
 - dump magnet, 700, 701
 - pulsed bending magnet, 694–697
 - quadrupole, 702, 703
 - steering, 697, 703
 - (*see also* Beam switchyard)
- Magnetic measurements, 637–643
- Magnetic shielding, 193–197
- Magnetron, 28, 29
- Magnets, beam switchyard, 617–649
 - costs, 637
 - data reduction of, 644–646
 - dc steering magnets, 635–637
 - description, 617–619
 - design, 619–621
 - dump magnet, 633–635
 - 8 cm quadrupoles, 626–629, 643
 - 8.6 cm quadrupoles, 645
 - 18.6 cm quadrupoles, 629–632, 643, 645
 - location, 646, 647
 - momentum analysis by, 647, 648
 - photon beam magnets, 637
 - pulsed, 621–623
 - pulsed steering magnets, 635
 - 3° bending, 623–626, 637–645
 - (*see also* Beam switchyard)
- Main booster amplifier (*see* Drive system)
- Main drive line (*see* Drive system)
- Mallory, K., 29, 32
- Manpower, 52
- Master oscillator (*see* Drive system)
- Master trigger generator, 476
- Measurements, magnetic, 637–643
- Mendelev, D. I., 10
- Messimer, R. C., 29
- Modulators, 69, 411–462
 - choice of type, 411, 412
 - de Q 'ing, 415, 427–436

- de-spiking network, 437–439
 - end of line clipper, 425–427
 - general description, 412–417
 - injector, 484
 - main, 411–453
 - power supplies, 418–423
 - pulse cable assembly, 451, 452
 - pulse forming network, 413–415, 423
424
 - pulse transformer, 448–451
 - sub-booster, 453–462
 - switch tubes, 439–446
 - thyratron trigger system, 446, 447
(*see also* Instrumentation and control)
- National laboratory, 3
- Neal, R. B., 29, 32
- Neilsen, I. R., 29
- Neutron, 10
- Nuclear atom, 10
- Oglesby, C., 33
- Operating results, initial, 82–84
- Operating statistics, 92–94
- Organisation, 39–45
- Oscillator, master (*see* Drive system)
- Page, B., 33
- Panofsky, W. K. H., 32
- Particles
 - basic laws, 12
 - classification schemes, 11
 - interactions forces, 11
 - intrinsic properties, 11
- Pattern, generator, 465, 484–488
- Pearson, P. A., 29
- Periodic table, 10
- Phase shifters, 396, 401, 402
- Phase velocity, 61, 62, 133
- Phasing, 70, 383–409
 - accuracy requirement, 272
 - beam induction method, 387–392
 - detectors for, 390–392
 - phase wobbling, 392–395
 - cables, 401
 - electronics, 404–406
 - energy spectrum as function of, 383,
384
 - procedures, 406, 407
 - programmer, 404
 - results, 407, 408
 - RF detectors, 402, 408
 - sector phasing equipment, 396–398
 - electronics, 392–395, 397, 398
 - operation, 398, 399
 - special features, 400, 401
 - techniques
 - beam energy maximization, 384,
385
 - direct phase comparison, 385
 - reactive beam loading, 386
 - resistive beam loading, 385, 386
- Photon, 10
- Physical plant, 1069–1158
 - initial construction, 1069–1071
 - installation of accelerator equipment,
1071–1085
 - planning and management, 1069–1088
 - recent construction, 1085–1088
- Pindar, F. V. L., 32
- Position monitors, 658–660
- Positron source, 72–74, 545–583
 - calculated yield, 549, 550
 - cooling water system, 959–968
 - description, 545, 546
 - focusing, 551–561, 572–576
 - girders, 857, 858
 - instrumentation and control, 577–581
 - operating experience, 581, 582
 - radiator, 547, 548
 - slug, 563, 564
 - wand, 565–568
 - wheel, 569–572
- Post, R. F., 29
- Power, electrical (*see* Electrical power system)
- Power supplies, magnet, 697–703
(*see also* Beam switchyard)
- Profile monitors, 660–666
 - Cerenkov light, 662, 663
 - optics and TV system, 665–667
 - synchrotron light, 660–662
 - zinc-sulfide screens, 664, 665
- Program Advisory Committee, 6, 37

- Protection collimators, 759–770
- Protection systems, 775–819
 - description, 781–791
 - design criteria, 779, 780
 - equipment, 810–819
 - long ion chamber, 814–817
 - manway monitors, 802
 - meteorological measurements, 808–810
 - operation, 792–794
 - peripheral monitoring, 798–801
 - personnel beam shutoff, 805, 806
 - radiation monitoring, 794–810
 - radioactive gas monitor, 804, 805
 - research area monitoring, 796–798
 - water monitor, 802, 803
(*see also* Interlocks)
- Proton accelerators, 2
- Pulse forming network (*see* Modulators)
- Pulse length, RF, and beam, 103, 104
- Pulse transformer (*see* Modulators)

- Q**, accelerator structure, 135

- Radiation**
 - damage to components, 606–608, 619, 652
(*see also* Shielding and radiation)
- Remote control system, 75
- Repetition rate, 104
- Research area, 81, 82, 1135–1150
- Research equipment, initial 22–24
- Research objectives, 9
- Research program
 - early, 18
 - elastic scattering, 18
 - experiments, 6, 7
 - muon scattering, 21
 - new particle search, 21
 - photoproduction, 20
 - strong-interaction experiments, 21
- Resonant accelerator, 27
- Rutherford, E., 10

- Scheduling, 45–47
- Schiff, L., 32

- Scientific Policy Committee, 4, 5, 36
- Secondary emission monitors, 667, 668
- Serebryakov, Y. N., 208
- Shielding, beam switchyard, 608, 609
- Shielding, magnetic, 193–197
- Shielding and radiation, 1029–1067
 - electromagnetic cascade, 1029–1032
 - muon production, 1047–1053
 - neutron production and attenuation, 1035–1040
 - neutron spectrum in penetrations, 1056, 1057
 - photon radiation, 1032–1035
 - photoneutron measurement, 1040–1047
 - radiation in tunnel and penetrations, 1053–1057
 - residual radiation, 1057–1062
 - shielding calculations, 1062, 1063
- Site and site improvements, 55–57, 1088–1094
 - erosion control, 1092, 1093
 - fencing and main entryway, 1095
 - geology, 1089, 1090
 - landscaping, 1093, 1094
 - roads, yards, and parking, 1091, 1092
 - site investigation program, 1088, 1089
 - soil mechanics, 1090, 1091
 - storm drainage, 1092

- SLAC**
 - as national facility, 3, 4
 - compared to other accelerators, 2
 - design and construction, 1
 - experimental scheduling policy, 4
 - general plan, 57–60
 - general policies, 4
 - operating statistics, 92–94
 - principles of operation, 60–63
 - Program Advisory Committee, 6
 - relationship to AEC, 7, 8
 - relationship to Stanford University, 7, 8
 - scheduling, 7
 - Scientific Policy Committee, 4, 5
 - site description, 55–57
- Slits, beam (*see* Collimators and slits)
- Soderstrom, J. C., 29
- Sonkin, S., 29, 32

- Spectrometers, 22–24
- Spectrum analyzer, 671, 672
- Stanford Linear Accelerator Center (*see* SLAC)
- Sterling, J. E. Wallace, 33
- Sub-booster klystron (*see* Drive system)
- sub-booster klystron and modulator (*see* Drive system)
- Sub-booster modulator
 - choice of switch tubes, 458, 459
 - circuit, 453–458
 - description, 453
 - driver circuit, 459, 460
 - fall time, 458
 - high-voltage regulator circuit, 462
 - main high-voltage supply, 461, 463
 - power supplies, 461
 - (*see also* Drive system)
- Sub-drive line (*see* Drive system)
- Support and alignment, 821–885
 - (*see also* Accelerator support system and Laser alignment system)
- Switchyard, beam, 79, 80, 585–615
- Symmetry, 11

- Test laboratory, 1101, 1102
- Transient behavior, accelerator structure, 123–125
- Transport system, beam, 166–192
- Transport system, beam switchyard (*see* Beam switchyard)
- Trigger system, 463–488
 - beam loading compensation, 472, 473
 - clock, 474–476
 - comparator, 476, 477
 - delays, 469–472
 - distribution, 465, 479, 480
 - generator
 - sector, 468, 469
 - standard, 467, 468
 - logic, 464, 465
 - master clock, 465
 - master trigger generator, 476
 - pattern generator, 465, 484–488
 - principles of operation, 463–465
 - programming for multiple beams, 465–467
 - sector trigger generator, 480–484
 - sequence generator, 475, 476
 - signal waveforms, 473, 474
 - switchyard trigger generator, 484
- Tune-up monitor, 670
- Tuning, accelerator structure, 136–142, 153–157

- Utilities, 1150–1156
 - central heating water, 1152, 1153
 - chilled water, 1153
 - compressed air, 1154
 - domestic water, 1151
 - natural gas, 1153, 1154
 - paging system, 1155, 1156
 - sewer system, 1152
 - telephone and radio, 1154–1156

- Vacuum systems, 70, 71, 887–933
 - accelerator, 888–913
 - beam line fast acting valves, 902–904
 - cryosorption roughing pumps, 908–911
 - design, 888, 889
 - gauges and controllers, 904–908
 - klystron gallery valves, 902
 - manifold piping, 899–902
 - operating experience, 912, 913
 - pumping speeds and pressures, 889–894
 - sputter-ion pumps, 897–899
 - sub-system, 894–897
 - alignment light pipe system, 913–916
 - description, 914, 915
 - design, 913–915
 - instrumentation and control, 914, 915
 - operating experience, 916
 - beam switchyard, 610, 916–929
 - beam-line fast-acting valves, 924–926
 - beam-line isolation valves, 924
 - design, 916, 917
 - differential pumping stations, 919, 920
 - diffusion pumping stations, 918, 919
 - divergent chambers, 920, 921
 - instrumentation and control, 926–929

- operating experience, 929–931
- pipng and bellows assemblies, 921, 922
- quick disconnect couplers, 923, 924
- sub-system arrangement, 917, 918
- Valves, vacuum
 - beam-line fast-acting, 902–904, 924–926
 - beam-line isolation, 924
 - klystron gallery, 902
 - waveguide vacuum, 362–364
- Variable voltage substation, 1001
- Varian, 27
- Voskresenkii, G. V., 208

- Water systems (*see* Cooling water systems)
- Waveguide, 345–382
 - design for higher energy, 346
 - dimensional stability, 351–355
 - directional couplers, 364–374
 - cross guide coupler, 373–374
 - modified Bethe hold coupler, 371–373
 - power divider, 367–371
 - flanges, 374–376
 - insulation and heat control, 355–357
 - layout, 346–350
 - loads, 377–381
 - mechanical mounting, 347, 348
 - phasing, 357–361
 - power dividers, 346, 347
 - selection of, 350–352
 - vacuum valves, 362–364
 - windows, 345, 346
- Windows, klystron, 320–337
- Windows, waveguide, 345, 346
- Woodyard, J. R., 27